

Liquid Faction — Standard Technical Rider & Stage Plot

Contact: Luke Roehrborn | LiquidFactionBand@gmail.com | 847-666-7612 [2]

Agency Representation: Bass/Schuler Entertainment [2]

This document outlines the standard technical specifications required for a 6-piece Liquid Faction live performance. Channels, lines, and microphone selections can be varied dependent on festival or house sound technician preference.

I. Main System Input Patch List

Ch. Instrument / Source Preferred Mic / DI			Stage Position / Notes
1	Guitar Amp (Luke)	Shure SM57 or equivalent	Stage Left (SL) [1]
2	Luke Vocal	Shure SM58 / Boom Stand Required	Stage Left (SL) [1]
3	Guitar Amp (Ricky)	Shure SM57 or equivalent	Stage Right (SR) [1]
4	Bass Amp (Sam)	Balanced XLR Direct Out (DI)	Stage Left (SL) [1]
5	Ricky Vocal	Shure SM58 / Wireless Preferred	Downstage [1]
6	Ian Vocal	Shure SM58 / Wireless Preferred	Downstage [1]
7	Gianna Vocal	Shure SM58 / Wireless Preferred	Downstage [1]
8	Kick Drum (Jeff)	Shure Beta 91A / Beta 52A	Upstage Center (USC) [1]
9	Snare Top	Shure SM57 or equivalent	Upstage Center (USC) [1]
10	Hi-Hat	AKG C451 or equivalent	Upstage Center (USC) [1]
11	Overhead (Stereo)	Matched Condenser Pair	Upstage Center (USC) [1]
12	Hi-Tom	Sennheiser e604 or equivalent	Upstage Center (USC) [1]
13	Mid-Tom	Sennheiser e604 or equivalent	Upstage Center (USC) [1]
14	Low-Tom	Sennheiser e604 or equivalent	Upstage Center (USC) [1]

II. Stage Monitoring & Monitor Mix Requirements

- **Total Mixes Required:** 6 separate, independent monitor mixes (6 discrete In-Ear Monitor sends).

- **Stage Footprint:** 100% silent stage monitoring footprint. No on-stage floor wedge monitors required.
- **In-Ear Monitors (IEM):** 6 separate wireless or wired IEM mix feeds required for all performing members: